

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF
THE DEPENDENT RESURVEY OF
A PORTION OF THE SALT LAKE BASE LINE,

PORTIONS OF THE WEST BOUNDARY,

AND

SUBDIVISIONAL LINES,

AND THE INTERIOR

SUBDIVISION LINES OF SECTIONS 3, 4, 5, 7, 8, 9, AND 10,

IN

TOWNSHIP 1 SOUTH, RANGE 7 WEST

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh
Supervisory Cadastral Surveyor

Under special instructions dated *August 11, 1995*, approved *August 15, 1995*, which provided for the surveys included under Group Number 827, and assignment instructions dated *August 18, 1995*.

Survey commenced *August 18, 1995*

Survey completed *September 6, 1995*

INDEX DIAGRAM

Township 1 South, Range 7 West

| | | | | | | | | | | |
|----|----|----|----|----|----|----|----|----|----|----|
| 4 | 4 | 4 | 4 | 3 | 3 | 3 | | | | |
| 6 | 14 | 5 | 11 | 4 | 9 | 3 | 7 | 2 | 1 | |
| | 14 | 14 | 11 | 11 | 8 | 9 | 6 | 6 | | |
| 5 | 7 | 13 | 8 | 10 | 9 | 8 | 10 | 6 | 11 | 12 |
| 5 | 14 | 13 | 13 | 10 | 10 | 8 | 7 | 7 | | |
| | 18 | 12 | 17 | | 16 | | 15 | | 14 | 13 |
| | 12 | | | | | | | | | |
| 19 | | 20 | | 21 | | 22 | | 23 | | 24 |
| | | | | | | | | | | |
| 30 | | 29 | | 28 | | 27 | | 26 | | 25 |
| | | | | | | | | | | |
| 31 | | 32 | | 33 | | 34 | | 35 | | 36 |

| | |
|------------------------------------|---------|
| The Subdivision of Section 3..... | Page 16 |
| The Subdivision of Section 4..... | Page 18 |
| The Subdivision of Section 5..... | Page 19 |
| The Subdivision of Section 7..... | Page 20 |
| The Subdivision of Section 8..... | Page 21 |
| The Subdivision of Section 9..... | Page 22 |
| The Subdivision of Section 10..... | Page 22 |

TOWNSHIP 1 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The following field notes describe the dependent resurvey of a portion of the Salt Lake Base Line, portions of the west boundary, subdivisional lines, and the interior subdivision lines of sections 3, 4, 5, 7, 8, 9, and 10, in T. 1 S., R. 7 W., Salt Lake Meridian, Utah.

History of SurveysSurveyed byRetr. or Resurveyed byNORTH BOUNDARY

| | | | | |
|---------|--------------|------|-------------------------|------|
| Portion | J. Gorlinski | 1871 | | |
| All | A.J. Stookey | 1906 | A.J. Stookey | 1906 |
| Portion | | | J.R. Stewart and Dalton | 1913 |

SOUTH BOUNDARY

| | | | | |
|---------|--------------|------|-------------------------|------|
| Portion | J. Gorlinski | 1871 | | |
| All | A.J. Stookey | 1906 | A.J. Stookey | 1906 |
| Portion | | | R.C. Yundt and D. Brown | 1937 |

EAST BOUNDARY

| | | | | |
|---------|--------------|------|-------------------------|------|
| All | A.J. Stookey | 1906 | | |
| Portion | | | J.R. Stewart and Dalton | 1913 |

WEST BOUNDARY

| | | | | |
|-----|--------------|------|--------------|------|
| All | J. Gorlinski | 1871 | | |
| All | | | A.J. Stookey | 1906 |

SUBDIVISION

| | | | | |
|-----|--------------|------|--|--|
| All | A.J. Stookey | 1906 | | |
|-----|--------------|------|--|--|

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 827, Utah, dated August 11, 1995.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportional positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

TOWNSHIP 1 SOUTH, RANGE 7 WEST, SALT LAKE MERIDIAN, UTAH

CHAINS

The directions of lines were determined by Global Positioning System (GPS) receivers and supplemented by references to the true meridians established on line by hour angle observations on the sun. The directions as given in the field notes are all forward bearings. Distance were determined by electronic distance measurement instruments, and GPS.

The geographic position of the corner of sections 10, 11, 14 and 15, as determined by Global Positioning Systems (GPS), is as follows:

Latitude 40° 44' 18.467" N. Longitude 112° 36' 30.371" W.
N.A.D. 1927

The mean magnetic declination is 14° East.

Dependent Resurvey of a Portion of the Salt Lake
Base Line on the North Boundary of T. 1 N., R. 7 W.,
Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by J. R. Stewart in 1913)

Beginning at the point for the standard corner of sections 34 and 35, on the Salt Lake Base Line in T. 1 N., R. 7 W., at proportionate distance; there is no remaining evidence of the original cor. Point falls in water and is not monumented.

From this point, the standard corner of sections 31 and 32, on the Salt Lake Base Line in T. 1 N., R. 6 W., bears S. 89° 58.7' E., 240.333 chains distance, monumented with an iron post extending 16 ins. above ground with cap marked:

T1N R6W
S31 | S32
1913

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

S C
T1N R6W
S31 | S32
T1S
1995

Deposit the old iron post alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SALT LAKE
BASE LINE ON THE NORTH BOUNDARY OF T. 1 N., R. 7 W.,
SALT LAKE MERIDIAN, UTAH

CHAINS

This corner has been designated as a BLM control station, with Latitude 40° 46' 04.737" N., and Longitude 112° 33' 03.046" W., determined by Global Positioning System (GPS). N.A.D. 1927.

N. 89° 58.7' W., along the south boundary of section 34.

1.532 Point for the closing corner of sections 2 and 3, T. 1 S., R. 7 W., at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.

40.055 Point for the standard 1/4 section corner of section 34, at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.

41.596 Point for the 1/4 section corner of section 3, T. 1 S., R. 7 W., at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.

80.110 The standard corner of sections 33 and 34, monumented with a limestone, 15x7x7 ins., firmly set and marked SC on N face. Other marks have been obliterated.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with brass cap marked:

S C
T1N R7W
S33 | S34
T1S
1995

Deposit the marked stone alongside the stainless steel post.

This corner has been designated as a BLM control station, with Latitude 40° 46' 04.817" N., and Longitude 112° 37' 37.824" W., determined by Global Positioning System (GPS). N.A.D. 1927

S. 89° 58.0' W., along the south boundary of section 33.

1.551 The closing corner of sections 3 and 4, T. 1 S., R. 7 W., monumented with a limestone, 23x7x5 ins., firmly set and plainly marked 3 grooves on the E and W faces, with CC on the S. face.

DEPENDENT RESURVEY OF A PORTION OF THE SALT LAKE
BASE LINE ON THE NORTH BOUNDARY OF T. 1 N., R. 7 W.,
SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

| | |
|---------|----|
| T1N | |
| C | C |
| S4 | S3 |
| T1S R7W | |
| 1995 | |

Deposit the marked stone alongside the stainless steel post.

- 40.056** Point for the standard 1/4 section corner of section 33, at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.
- 41.627** Point for the 1/4 section corner of section 4, T. 1 S., R. 7 W., at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.
- 80.112** Point for the standard corner of sections 32 and 33, at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.
-
- S. 89° 58.4' W., along the south boundary of section 32.
- 1.591** Point for the closing corner of sections 4 and 5, T. 1 S., R. 7 W., at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.
- 21.619** Point for the E 1/16 section cor of section 5, T. 1 S., R. 7 W. Point falls in water and is not monumented.
- 40.046** Point for the standard 1/4 section corner of section 32, at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.
- 41.647** Point for the 1/4 section corner of section 5, T. 1 S., R. 7 W., at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.
- 80.112** Point for the standard corner of sections 31 and 32, at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.
-

DEPENDENT RESURVEY OF A PORTION OF THE SALT LAKE
BASE LINE ON THE NORTH BOUNDARY OF T. 1 N., R. 7 W.,
SALT LAKE MERIDIAN, UTAH

CHAINS

S. 89° 58.0' W., along the south boundary of section 31.

1.591 Point for the closing corner of sections 5 and 6, T. 1 S., R. 7 W., at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.

40.056 Point for the standard 1/4 section corner of section 31, at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.

From this point, the standard corner of sections 34 and 35, on the Salt Lake Base Line in T. 1 N., R. 8 W., bears S. 89° 58.0' W., 200.400 chains distance, monumented with a quartzite stone, 20x9x6 ins. firmly set and marked 2 grooves on the E. and 4 grooves on the W. and SC on the N. faces.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground with brass cap marked:

S C
T1N R8W
S34 | S35
T1S
1995

Deposit the marked stone alongside the stainless steel post.

This corner has been designated as a BLM control station, with Latitude 40° 46' 04.662" N., and Longitude 112° 43' 21.411" W., determined by Global Positioning System (GPS).
N.A.D. 1927

Dependent Resurvey of a Portion of the West Boundary,
T. 1 S., R. 7 W., Salt Lake Meridian, Utah.

(Reestablishment of the Resurvey Executed by A. J. Stookey in 1906)

From the corner of sections 7, 12, 13, and 18, on the west boundary of the township, monumented with a limestone, 18x6x5 ins., firmly set and marked 4 notches on the S. and 2 notches on the N. edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY,
T. 1 N., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T1S
R8W R7W
S12 | S7
S13 | S18
1995

Deposit the marked stone alongside the stainless steel post.

N. 0° 01.5' W., between sections 7 and 12.

40.174 The 1/4 section corner of sections 7 and 12, monumented with a limestone, 15x8x3 ins., firmly set and marked 1/4 on W. face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

T1S
R8W R7W
1/4
S12 | S7
1995

Deposit the marked stone alongside the stainless steel post.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 1 S., R. 7 W., Salt Lake Meridian, Utah

(Reestablishment of the Survey Executed by A.J. Stookey in 1906)

From the 1/4 section corner of sections 10 and 11, monumented with a black quartzite stone, 18x9x5 ins., (record, limestone, 15x6x6 ins.) firmly set and marked 1/4 on W. face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap marked:

T1S R7W
1/4
S10 | S11
1995

Deposit the marked stone alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 05.2' E., between sections 10 and 11.

40.174

Point for the corner of sections 2, 3, 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap marked:

| | |
|-----------|-----------|
| T1S R7W | |
| <u>S3</u> | <u>S2</u> |
| S10 | S11 |
| 1995 | |

From the 1/4 section corner of sections 2 and 11, monumented with a black quartzite stone, 16x9x4 ins., (record, limestone, 15x8x5 ins.) encrusted in the salt deposit and 18 ins. under water, marked 1/4 on one side.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

| | |
|-----|-----------|
| | T1S R7W |
| | <u>S2</u> |
| 1/4 | S11 |
| | 1995 |

Deposit the marked stone alongside the stainless steel post.

S. 89° 50.6' W., between sections 2 and 11.

39.982

The corner of sections 2, 3, 10, and 11.

N. 0° 05.0' W., between sections 2 and 3.

40.174

Point for the 1/4 section corner of sections 2 and 3, at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.

82.808

The point for the closing corner of sections 2 and 3, on the Salt Lake Base Line, hereinbefore described.

From the corner of sections 10, 11, 14, and 15, monumented with a black quartzite stone, 19x5x4 ins., (record, limestone, 15x9x5 ins.) firmly set and marked 2 notches on the E. edge.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap marked:

| | |
|------------|------------|
| T1S R7W | |
| <u>S10</u> | <u>S11</u> |
| S15 | S14 |
| 1995 | |

Deposit the marked stone alongside the stainless steel post.

This corner has been designated as a BLM control station, hereinbefore described.

S. 89° 57.8 W., between sections 10 and 15.

39.919 Point for the 1/4 section corner of sections 10 and 15, at proportionat distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked:

| | |
|-----|------------|
| | T1S R7W |
| | <u>S10</u> |
| 1/4 | S15 |
| | 1995 |

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of corner

Corner is located between the east bound lane and S. right-of-way fence.

79.838 The corner of sections 9, 10, 15, and 16, monumented with a black quartzite stone, 13x11x2 ins., (record, 18x8x4 ins.), firmly set and marked 1 notch on S. edge. Others have been obliterated.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins diam., 24 ins. in the ground, with brass cap marked:

| | |
|-----------|------------|
| T1S R7W | |
| <u>S9</u> | <u>S10</u> |
| S16 | S15 |
| 1995 | |

Deposit the marked stone alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 9 and 10, monumented with a limestone, 18x10x6 ins., firmly set and plainly marked 1/4 on W. face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked:

T1S R7W
1/4
S9 | S10
1995

Deposit the marked stone alongside the stainless steel post.

From this corner, the tri-station "TIMPIE" bears, S. 65° 53' 46" W., 36.083 chains dist., monumented with a standard tablet stamped "TIMPIE 1958" cemented in rock outcrop.

N. 0° 11.1' W., between sections 9 and 10.

40.329 The corner of sections 3, 4, 9, and 10, monumented with a black quartzite stone, 23x8x6 ins., (record, 18x6x6 ins.), submerged in mud and aquatic grass, 24 ins. below the water surface, marked 3 notches on one edge.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins diam., 24 ins. in the ground, with brass cap marked:

T1S R7W
S4 | S3
S9 | S10
1995

Deposit the marked stone alongside the stainless steel post.

From the corner of sections 2, 3, 10, and 11.

S. 89° 53.7 W., between sections 3 and 10.

39.973 The 1/4 section corner of sections 3 and 10, monumented with a black quartzite stone, 13x6x6 ins., (record, 15x6x6 ins.) projecting 5 ins. above ground, firmly set and marked 1/4 on S. face.

At the corner point

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap marked:

T1S R7W
1/4 S3
 S10
 1995

Deposit the marked stone alongside the stainless steel post.

N. 89° 42.0' W., beginning new measurement.

39.987 The corner of sections 3, 4, 9, and 10.

N. 0° 16.2' W., between sections 3 and 4.

40.124 The 1/4 section corner of sections 3 and 4, monumented with an unmarked black quartzite stone, 14x5x4 ins., (record, 15x7x5 ins.) loosely set and projecting 5 ins above ground.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked:

T1S R7W
1/4
S4 | S3
1995

Deposit the unmarked stone alongside the stainless steel post.

N. 0° 09.7' W., beginning new measurement.

20.073 Point for the N 1/16 section corner of sections 3 and 4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

T1S R7W
N 1/16
S4 | S3
1995

42.585 The closing corner of sections 3 and 4, hereinbefore described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the corner of sections 9, 10, 15, and 16.

N. 89° 58.5' W., between sections 9 and 16.

- 40.141** The 1/4 section corner of sections 9 and 16, monumented with a limestone, 15x7x5 ins., firmly set and marked 1/4 on N. face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base to top of brass cap marked:

| | |
|-----|-----------|
| | T1S R7W |
| 1/4 | <u>S9</u> |
| | S16 |
| | 1995 |

Deposit the marked stone alongside the stainless steel post.

N. 89° 37.8' W., beginning new measurement.

- 40.446** The corner of sections 8, 9, 16, and 17, monumented with a limestone, 20x12x9 ins., firmly set and marked 4 notches on the S. and E. edges.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24ins. in the ground, with aluminum cap marked:

| | |
|--|----------------|
| | T1S R7W |
| | <u>S8 S9</u> |
| | S17 S16 |
| | 1995 |

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner

The corner is located about 50 links W. of a N and S dirt road.

N. 0° 01.9' W., between sections 8 and 9.

- 40.174** Point for the 1/4 section corner of sections 8 and 9, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T1S R7W

1/4

S8 | S9

1995

Corner falls at the toe of slope of the off ramp, of the west bound lane of freeway.

80.348 The corner of sections 4, 5, 8, and 9, monumented with a broken limestone, 14x7x5 ins., set and marked 5 notches on the S. and 4 notches on the E. edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked:

T1S R7W

S5 | S4

S8 | S9

1995

Deposit the marked stone alongside the stainless steel post.

From the corner of sections 3, 4, 9, and 10.

S. 89° 30.5' W., between sections 4 and 9.

40.206 The 1/4 section corner of sections 4 and 9, monumented with a black limestone, 18x7x7 ins., firmly set and marked 1/4 on N face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked:

T1S R7W

1/4 S4

S9

1995

Deposit the marked stone alongside the stainless steel post.

N. 89° 16.5' W., beginning new measurement.

40.307 The corner of sections 4, 5, 8, and 9.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 08.0' E., between sections 4 and 5.

39.559

The 1/4 section corner of sections 4 and 5, monumented with a black quartzite stone, 14x6x3 ins., (record 15x6x6 ins.), dimly marked 1/4 on W. face, and loosely set with a wooden stake alongside.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, encircled by a collar of stone, with brass cap marked:

T1S R7W
1/4
S5 | S4
1995

Deposit the marked stone alongside the stainless steel post.

N. 0° 04.3' W., beginning new measurement.

20.273

Point for the N 1/16 section corner of sections 4 and 5.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

T1S R7W
N 1/16
S5 | S4
1995

42.938

Point for the closing corner of sections 4 and 5, hereinbefore described.

From the corner of sections 17, 18, 19 and 20, monumented with a limestone, 22x7x7 ins., set and marked 3 notches on the S. and 5 notches on the E. edges and in a small mound of stone.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap marked:

T1S R7W
S18 | S17
S19 | S20
1995

Deposit the marked stone alongside the stainless steel post.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

N. 0° 01.8' W., between sections 17 and 18.

40.162

The 1/4 section corner of sections 17 and 18, monumented with a black limestone, 14x7x6 ins., set and dimly marked 1/4 on W. face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap marked:

T1S R7W
1/4
S18 | S17
1995

Deposit the marked stone alongside the stainless steel post.

N. 0° 04.8' W., beginning new measurement.

40.130

Point for the corner of sections 7, 8, 17, and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 30 ins. long, 2 1/2 ins., diam., 24 ins. in the ground, and in a collar of stone, with brass cap marked:

T1S R7W
S7 | S8
S18 | S17
1995

From the corner of sections 8, 9, 16, and 17.

N. 89° 51.7' W., between sections 8 and 17.

40.048

Point for the 1/4 section corner of sections 8 and 17, at proportionate distance; there is no remaining evidence of the original corner

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

1/4 T1S R7W
S8
S17
1995

80.096

The corner of sections 7, 8, 17, and 18.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

North, between sections 7 and 8.

40.130

The 1/4 section corner of sections 7 and 8, monumented with a limestone, 15x6x6 ins., firmly set and marked 1/4 on W. face.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

T1S R7W

1/4

S7 | S8

1995

Deposit the marked stone alongside the stainless steel post.

From the corner of sections 4, 5, 8, and 9.

N. 89° 55.0' W., between sections 5 and 8.

20.016

Point for the E 1/16 section corner of sections 5 and 8.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked:

T1S R7W

E 1/16

S5

S8

1995

Corner is located about 2 ft. W. of N and S fence.

40.032

Point for the 1/4 section corner of sections 5 and 8, at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.

80.064

The corner of sections 5, 6, 7, and 8, monumented with a limestone, 18x7x5 ins., firmly set and marked 5 notches on the S. and E. edges.

At the corner point

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL
LINES, T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T1S R7W

S6 | S5

S7 | S8

1995

Deposit the marked stone alongside the stainless steel post.

N. 0° 02.0' W., between sections 5 and 6.

40.080 Point for the 1/4 section corner of sections 5 and 6, at proportionate distance; there is no remaining evidence of the original corner. Point falls in water and is not monumented.

82.344 The point for the closing corner of sections 5 and 6, hereinbefore described.

From the corner of sections 7, 8, 17, and 18.

N. 89° 52.5' W., between sections 7 and 18.

40.058 The 1/4 sections corner of sections 7 and 18, monumented with alimestone, 15x7x4 ins., firmly set and marked 1/4 on N. face.

At the corner point

Set an aluminum post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

T1S R7W

1/4 S7

S18

1995

Deposit the marked stone alongside the aluminum post.

N. 89° 53.5' W., beginning new measurement.

39.751 The corner of sections 7, 12, 13, and 18, on the west boundary of the township, hereinbefore described.

The Subdivision of Section 3,
T. 1 S., R. 7 W., Salt Lake Meridian, Utah

THE SUBDIVISION OF SECTION 3,
T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

From the 1/4 section corner of sections 3 and 10.

N. 0° 09.3' W., on the N-S center line of section 3.

40.290 Point for the center 1/4 section corner of section 3, at intersection with the E-W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

T1S R7W
C 1/4 S3
1995

Set one single stone alongside the stainless steel post.

60.370 Point for the center N 1/16 section corner of section 3.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

C
N 1/16 | S3
C
1995

The corner is located in water, with 3 stones alongside the stainless steel post, and just S. of barrow pit.

82.900 The point for the N 1/4 section corner of section 3, hereinbefore described.

From the point for the 1/4 section corner of sections 2 and 3.

N. 89° 56.1' W., on the E-W center line of section 3.

40.018 The center 1/4 section corner of section 3.

80.081 The 1/4 section corner of sections 3 and 4.

From the center N. 1/16 section corner of section 3.

N. 89° 57.2' W., on the E-W center line of the NW 1/4.

40.064 The N. 1/16 section corner of sections 3 and 4.

THE SUBDIVISION OF SECTION 4,
T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 4,
T. 1 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 4 and 9.

N. 0° 07.7' W., on the N-S center line of section 4.

40.271 Point for the center 1/4 section corner of section 4, at intersection with the E-W center line.
Point falls in water and is not monumented.

60.443 Point for the center N 1/16 section corner of section 4.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

C
N 1/16 | S4
C
1995

Corner falls in about a foot of water.

83.030 The point for the N 1/4 section corner of section 4, hereinbefore described.

From the 1/4 section corner of sections 3 and 4.

S. 89° 43.1' W., on the E-W center line of section 4.

40.102 The point for the center 1/4 section corner of section 4.

80.220 The 1/4 section corner of sections 4 and 5.

From the N 1/16 section corner of sections 3 and 4.

S. 89° 51.6' W., on the E-W center line of the NE 1/4 of section 4.

40.088 The center N 1/16 section corner of section 4.

S. 89° 51.4' W., on the E-W center line of the NW 1/4 of section 4.

40.096 The N 1/16 section corner of sections 4 and 5.

THE SUBDIVISION OF SECTION 5,
T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 5,
T. 1 S., R. 7 W., Salt Lake Meridian, Utah

From the point for the 1/4 section corner of sections 5 and 8.

N. 0° 00.2' W., on the N-S center line of section 5.

39.819 Point for the center 1/4 section corner of section 5, at intersection with the E-W center line.
Point falls in water and is not monumented.

59.975 Point for the center N 1/16 section corner of section 5, not monumented.

82.418 The point for the N 1/4 section corner of section 5, hereinbefore described.

From the 1/4 section corner of sections 4 and 5.

N. 89° 32.7' W., on the E-W center line of section 5.

20.065 Point for the center E 1/16 section corner of section 5.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

C — E 1/16 — C
S5
1995

40.130 The point for the center 1/4 section corner of section 5.

80.174 The point for the 1/4 section corner of sections. 5 and 6.

From the center E 1/16 section corner of section 5.

N. 0° 02.3' W., on the N-S center line of the NE 1/4 of section 5.

20.215 Point for the NE 1/16 section corner of section 5, at intersection with the E-W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap marked:

NE 1/16
S5
1995

THE SUBDIVISION OF SECTION 5,
T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS**42.770**

The point for the E 1/16 section corner of section 5, hereinbefore described.

From the N 1/16 section corner of sections 4 and 5.

N. 89° 42.8' W., on the E-W center line of the NE 1/4 of section 5.

20.048

The NE 1/16 section corner of section 5.

40.096

The point for the center N 1/16 section corner of section 5.

From the E 1/16 section corner of sections 5 and 8.

N. 0° 03.9' E., on the N-S center line of the SE 1/4 of section 5.

39.689

The center E 1/16 section corner of section 5.

The Subdivision of Section 7,
T. 1 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 7 and 18.

N. 0° 04.7' W., on the N-S center line of section 7.

40.149

Point for the center 1/4 section corner of section 7, at intersection with the E-W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap marked:

T1S R7W
C 1/4 S7
1995

80.286

The 1/4 section corner of sections 6 and 7.

From the 1/4 section corner of sections 7 and 8.

N. 89° 50.9' W., on the E-W center line of section 7.

40.107

The center 1/4 section corner of section 7.

79.816

The 1/4 section corner of sections 7 and 12 on the west boundary of the township.

THE SUBDIVISION OF SECTION 8,
T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 8,
T. 1 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 8 and 17.

N. 0° 01.6' W., on the N-S center line of section 8.

40.156 Point for the center 1/4 section corner of section 8, at intersection with the E-W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 22 ins. in the ground and in a collar of stone, with brass cap marked:

T1S R7W
C 1/4 S8
1995

80.310 The point for the 1/4 section corner of sections 5 and 8.

From the 1/4 section corner of sections 8 and 9.

N. 89° 53.6' W., on the E-W center line of section 8.

20.020 Point for the center E 1/16 section corner of section 8.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground and in a collar of stone, with brass cap marked:

T1S R7W
C — E 1/16 — C
S8
1995

40.040 The center 1/4 section corner of section 8.

80.065 The 1/4 section corner of sections 7 and 8.

From the center E 1/16 section corner of section 8.

N. 0° 01.7' W., on the N-S center line of the NE 1/4 of section 8.

40.166 The E 1/16 section corner of sections 5 and 8.

THE SUBDIVISION OF SECTION 9,
T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

The Subdivision of Section 9,
T. 1 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 9 and 16.

N. 0° 07.6' W., on the N-S center line of section 9.

40.276 Point for the center 1/4 section corner of section 9, at intersection with the E-W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground and in a collar of stone, with brass cap marked:

T1S R7W
C 1/4
S9
1995

80.099 The 1/4 section corner of sections 4 and 9.

From the 1/4 section corner of sections 9 and 10.

N. 89° 46.2' W., on the E-W center line of section 9.

40.254 The center 1/4 section corner of section 9.

80.628 The 1/4 section corner of sections 8 and 9.

The Subdivision of Section 10,
T. 1 S., R. 7 W., Salt Lake Meridian, Utah

From the 1/4 section corner of sections 10 and 15.

N. 0° 01.2' W., on the N-S center line of section 10.

40.115 Point for the center 1/4 section corner of section 10, at intersection with the E-W center line.

Set a stainless steel post, 30 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap marked:

THE SUBDIVISION OF SECTION 10,
T. 1 S., R. 7 W., SALT LAKE MERIDIAN, UTAH

CHAINS

T1S R7W
C 1/4
S10
1995

80.222 The 1/4 section corner of sections 3 and 10.

From the 1/4 section corner of sections 10 and 11.

S. 89° 59.3' W., on the E-W center line of section 10.

39.904 The center 1/4 section corner of section 10.

79.778 The 1/4 section corner of sections 9 and 10.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| Name | Capacity |
|-----------------|--------------------------------|
| Ferrel Reynolds | Surveying Technician |
| Frank Profaizer | Supervisory Cadastral Surveyor |
| Rod Ficklin | Engineering Technician |
| Justin Dolling | Engineering Technician |
| M. Ross Workman | Supervisory Cadastral Surveyor |

CERTIFICATE OF SURVEY

I, *Ronald K. Baugh*, *Supervisory Cadastral Surveyor*, hereby certify upon honor that, in pursuance of special instructions bearing the date of the *11th day of August, 1995*, I have *dependently resurveyed a portion of the Salt Lake Base Line, portions of the west boundary, and subdivisional lines, and the interior subdivision lines of sections 3, 4, 5, 7, 8, 9, and 10, in Township 1 South, Range 7 West*,

of the *Salt Lake Meridian*, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 18, 1996

Date

Ronald K. Baugh
(Cadastral Surveyor)

Date

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The foregoing field notes of the *dependent resurvey of a portion of the Salt Lake Base Line, portions of the west boundary and subdivisional lines, and the interior subdivision lines of sections 3, 4, 5, 7, 8, 9, and 10, Township 1 South, Range 7 West, Salt Lake Meridian, Utah*,

executed by *Ronald K. Baugh*, *Supervisory Cadastral Surveyor*

having been critically examined and found correct, are hereby approved

April 18, 1996

Date

Donald H. Fisher

(Chief Cadastral Surveyor, Utah State Office)